




- Consistency – Enstron has no voids, delamination, or hidden imperfections. It eliminates call backs because of underlayment failures.
- Smooth Surface – Sanded at 100 grit, to a tolerance +/- 0.005. This reduces patching and sanding, and saves installation time.
- Surface Hardness – At 46 lbs/cu. ft of density, Enstron is twice as dense as luan plywood. It deflects and reduces unexpected damage.
- Enstron is available in a variety of thicknesses and sizes. There is a thickness and size available to complete any flooring install.
- Enstron is approved as a substrate for hardwood flooring installations. One underlayment covers a variety of underlayment needs.



401 N. Pottlatch Rd. | Post Falls, ID 83854  
Tel (208) 777-2202 | [PlummerForestProducts.com](http://PlummerForestProducts.com)  
Steven Brickey, National Sales Manager



## PLUMMER FOREST PRODUCTS



### Resilient Floor Underlayment

Enstron Underlayment from Plummer Forest Products is the most environmentally friendly underlayment choice in the flooring market today. For over 20 years, Enstron has been the substrate for over 100 million square feet of successful floor installations. No other underlayment combines 100% recycled fiber, and formaldehyde-free construction, with a 15 year warranty. Enstron is made in the USA, and is readily available throughout North America. Its combination of price and performance is unmatched in North America.

- Formaldehyde Free
- Moisture Resistance
- Certified Recycled
- TSCA Title VI compliant, and CARB Exempt N-002-20B
- 15 Year limited Warranty

Visit [PlummerForestProducts.com](http://PlummerForestProducts.com) for more information and Installation Instructions.